

2

# **TC-1000 CLEAR 4 CHROME**

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier:	TC-1000 CLEAR 4 CHROME
SDS Number:	TC-1000 CLEAR 4 CHROME
Supplier Details:	REFLECTION IN PAINT 1203 E 58th Place Los Angeles, CA 90001
Phone:	(323) 231-3957
Fax:	(323) 231-3987
Emergency:	CHEMTREC (800) 424-9300

## HAZARDS IDENTIFICATION

#### **Classification of the Substance or Mixture**

#### GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Liquids, 1 Physical, Flammable Liquids, 2 Physical, Flammable Liquids, 3 Health, Acute toxicity, 4 Oral Health, Skin corrosion/irritation, 2 Health, Skin corrosion/irritation, 3 Health, Respiratory or skin sensitization, 1 Skin Health, Serious Eye Damage/Eye Irritation, 2 A Health, Acute toxicity, 4 Inhalation Health, Acute toxicity, 5 Inhalation Health, Respiratory or skin sensitization, 1 Respiratory Health, Specific target organ toxicity - Single exposure, 3 Environmental, Hazards to the aquatic environment - Acute, 2 Environmental, Hazards to the aquatic environment - Acute, 3 Environmental, Hazards to the aquatic environment - Chronic, 2 Environmental, Hazards to the aquatic environment - Chronic, 3

#### GHS Label Elements, Including Precautionary Statements

#### GHS Signal Word: DANGER

#### GHS Hazard Pictograms:



#### GHS Hazard Statements:

- H224 Extremely flammable liquid and vapour
- H225 Highly flammable liquid and vapour
- H226 Flammable liquid and vapour
- H302 Harmful if swallowed
- H315 Causes skin irritation
- H316 Causes mild skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H333 May be harmful if inhaled
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H336 May cause drowsiness or dizziness
- H401 Toxic to aquatic life
- H402 Harmful to aquatic life
- H411 Toxic to aquatic life with long lasting effects
- H412 Harmful to aquatic life with long lasting effects

#### **GHS Precautionary Statements:**

- P210 Keep away from heat/sparks/open flames/hot surfaces.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER or doctor/ physician if you feel unwell.
- P321 Specific treatment (see supplemental first aid instructions on this label).
- P330 Rinse mouth.
- P332 + P313 If skin irritation occurs: Get medical advice/ attention.
- P337 + P313 If eye irritation persists: Get medical advice/ attention.
- P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.
- P362 Take off contaminated clothing and wash before reuse.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
- P391 Collect spillage.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

3

4

P501 - Dispose of contents/ container to an approved waste disposal plant.

COMPOSITION/INFORMATION OF INGREDIENTS

	Cl	hemical In	ngredients
	CAS#	%	Chemitcal Name
	763-69-9	1-10%	Propanoic acid, 3-ethoxy-, ethvl ester
28	182-81-2	10-15%	Hexane, 1,6-diisocyanato-, homopolymer
	123-86-4	5-10%	Butyl acetates
	98-56-6	25-35%	Benzene, 1-chloro-4- (trifluoromethyl)-
	67-64-1	15-20%	Acetone

# FIRST AID MEASURES

General information; Ingestion: Get medical advice/attention.

5	FIRE FIGHTING MEASURES
Eye contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes !Vhile removing contaminated clothing and shoes.
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. Perform artificial respiration if breathing has stopped. Get medical attention.
	DO NOT induce vomiting. Get medical attention immediately. Never give liquid to an unconscious person

General Fire Hazards: Fight fire from a protected location. Wear self-contained breathing apparatus and protective clothing. Suitable (and unsuitable) extinguishing media

Suitable extinguishing Use: Alcohol resistant foam. Carbon dioxide or dry powder.

media:

Unsuitable extinguishing media: No data available.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash

back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures Vapors are heavier than air and may spread near ground to sources of ignition. Special protective equipment for Firefighters: firefighters must use standard protective equipment Including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Use personal protective equipment. Keep unauthorized personnel away.
Methods and material for containment and cleaning up:	All equipment used when handling the product must be grounced. Eliminate sources of Ignition. Absorb spillage with non-combustiible, absorbent material.
Notification Procedures:	Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas Stop the flow of material, if this is without risk.
Environmental Precautions:	Avoid release to the environment. Do not contaminate water sources or sewer.

# 7 HANDLING AND STORAGE Handling Precautions: Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling Keep away from heat, hot surfaces, sparks, open flames and other ig it ion sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static dischar es. Flammable/combustible: Keep away from oxidizers, heat and fames. Storage Requirements: Conditions for safe storage, Store in a well-ventilated place, Store in a cool place. Including any incompatibilities:

#### EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Personal Protective</b>
Equipment:

8

Propanoic acid, 3-ethoxy-, ethyl ester cas#:(763-69-9) [1-10%]

Personal protective equipment

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Hexane, 1,6-diisocyanato-, homopolymer cas#:(28182-81-2) [10-15%]

Personal protective equipment

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Butyl acetates cas#:(123-86-4) [5-10%]

Personal protective equipment

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min Material tested:Camatril (KCL 730 / Aldrich Z677442, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Benzene, 1-chloro-4-(trifluoromethyl)- cas#:(98-56-6) [25-35%]

Personal protective equipment

Eye/face protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection: impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Acetone cas#:(67-64-1) [15-20%]

Personal protective equipment

Eye/face protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact: Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject (KCL 897 / Aldrich Z677647, Size M)

Splash contact: Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject (KCL 897 / Aldrich Z677647, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection: impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi- purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Propanoic acid, 3-ethoxy-, ethyl ester cas#:(763-69-9) [1-10%]

Hexane, 1,6-diisocyanato-, homopolymer cas#:(28182-81-2) [10-15%]

Butyl acetates cas#:(123-86-4) [5-10%]

Components with workplace control parameters

TWA 150 ppm USA. ACGIH Threshold Limit Values (TLV) Eye & Upper Respiratory Tract irritation

STEL 200 ppm USA. ACGIH Threshold Limit Values (TLV) Eye & Upper Respiratory Tract irritation

TWA 150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -710 mg/m3 1910.1000

STEL	200 ppm 950 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
TWA	150 ppm 710 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants
The va	alue in mg/m3 is a	pproximate.
TWA	150 ppm 710 mg/m3	USA. NIOSH Recommended Exposure Limits
ST	200 ppm 950 mg/m3	USA. NIOSH Recommended Exposure Limits

Benzene, 1-chloro-4-(trifluoromethyl)- cas#:(98-56-6) [25-35%]

Acetone cas#:(67-64-1) [15-20%]

Components with workplace control parameters

 TWA
 500 ppm
 USA. ACGIH Threshold Limit Values (TLV)

 Eye & Upper Respiratory Tract irritation
 Central Nervous System impairment

 Hematologic effects
 Substances for which there is a Biological Exposure Index or Indices (see BEI section)

 Not classifiable as a human carcinogen

STEL 750 ppm USA. ACGIH Threshold Limit Values (TLV) Eye & Upper Respiratory Tract irritation Central Nervous System impairment Hematologic effects Substances for which there is a Biological Exposure Index or Indices (see BEI section) Not classifiable as a human carcinogen

STEL1,000 ppmUSA. OSHA - TABLE Z-1 Limits for2,400 mg/m3Air Contaminants - 1910.1000The acetone STEL does not apply to the cellulose acetate fiberindustry. It is in effect for all other sectors.

TWA 1,000 ppm USA. Occupational Exposure Limits 2,400 mg/m3 (OSHA) - Table Z-1 Limits for Air Contaminants

The value in mg/m3 is approximate.

- TWA250 ppmUSA. NIOSH Recommended590 mg/m3Exposure LimitsTWA750 ppmUSA. OSHA TABLE Z-1 Limits for
- 1,800 mg/m3 Air Contaminants 1910.1000
  - 9

PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Appearance	No information
Odor	No information
Color	No information
Odor Threshold	No information
pH value	No information
Melting point/freezing point	: No information
Boiling point / boiling range	56.05 °C / 133 °F
flash point	-17 °C / 1 °F
Evaporation rate	No information
Flammability (solid, gas)	No information
Evaporation limit in Air	
Upper flammability limit:	No information
Lower flammability limit:	No information
Vapor Pressure	No information
Vapor density	No information
Density(lbs per US gallon	9lbs
Specific gravity	1.08
Solubility(ies)	No information
Partition coefficient	No information
Auto ignition temperature	No information
<b>Decomposition temperature</b>	No information
Kinematic viscosity	No information
Dynamic viscosity	No information
Solid by weight	32.2%
Solid per gallon	3.0 pounds
Weight per gallon	9 lbs/gallon
Material VOC	100 grams per liter
Coating VOC	250 grams per liter

# **STABILITY AND REACTIVITY**

Reactivity:No data available.Chemical Stability:StableConditions to Avoid:Keep away from heat, sparks and open flame.Materials to Avoid:Oxidizern, acidsHazardous Decomposition:Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors

#### TOXICOLOGICAL INFORMATION

Propanoic acid, 3-ethoxy-, ethyl ester cas#:(763-69-9) [1-10%]

Information on toxicological effects

10

11

Acute toxicity: Oral LD50 LD50 Oral - rat - male - > 5,000 mg/kg LD50 Oral - rat - female - 4,309 mg/kg Inhalation LC50 LC50 Inhalation - rat - male - 6 h - > 998 ppm Dermal LD50 LD50 Dermal - rabbit - male - 4,080 mg/kg LD50 Dermal - rabbit - female - 4,680 mg/kg Other information on acute toxicity no data available

Skin corrosion/irritation: Skin - rabbit - No skin irritation - 4 h - OECD Test Guideline 404

Serious eye damage/eye irritation: Eyes - rabbit - No eye irritation - 24 h - OECD Test Guideline 405

Respiratory or skin sensitisation: guinea pig - Does not cause skin sensitisation. - OECD Test Guideline 406

Germ cell mutagenicity: Genotoxicity in vitro - S. typhimurium - with and without metabolic activation - negative

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Nausea, Headache, Vomiting, Central nervous system depression, Dizziness

Synergistic effects: no data available

Additional Information:

Repeated dose toxicity - rat - male and female - Oral - No observed adverse effect level - 1,000 mg/kg RTECS: UF3325000

Hexane, 1,6-diisocyanato-, homopolymer cas#:(28182-81-2) [10-15%]

Information on toxicological effects

Acute toxicity: Oral LD50 no data available Inhalation LC50 Dermal LD50 Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes: no data available

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be

harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

**RTECS:** Not available

Butyl acetates cas#:(123-86-4) [5-10%]

Information on toxicological effects

Acute toxicity: Oral LD50 LD50 Oral - rat - 10,700 - 14,130 mg/kg Inhalation LC50 LC50 Inhalation - rat - 4 h - > 21.0 mg/l Dermal LD50 LD50 Dermal - rabbit - 17,600 mg/kg Other information on acute toxicity no data available

Skin corrosion/irritation: Skin - rabbit - Skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit - Moderate eye irritation

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: Developmental Toxicity - rat - Inhalation:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Specific Developmental Abnormalities: Musculoskeletal system.

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: Drowsiness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: AF7350000

#### Benzene, 1-chloro-4-(trifluoromethyl)- cas#:(98-56-6) [25-35%]

Information on toxicological effects

Acute toxicity: LD50 Oral - rat - 13,000 mg/kg Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: Human Embryo Unscheduled DNA synthesis

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: XS9145000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Acetone cas#:(67-64-1) [15-20%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 5,800 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Tremor. LC50 Inhalation - rat - 8 h - 50,100 mg/m3 Inhalation: no data available

LD50 Dermal - guinea pig - 7,426 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit Result: Eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

# 12 ECOLOGICAL INFORMATION

Propanoic acid, 3-ethoxy-, ethyl ester cas#:(763-69-9) [1-10%]

Information on ecological effects

Toxicity:

Toxicity to fish static test LC50 - Pimephales promelas (fathead minnow) - 55.3 mg/l - 96 h. Method: OECD Test Guideline 203 static test LC50 - Pimephales promelas (fathead minnow) - 45.3 mg/l - 96 h Toxicity to daphnia Immobilization EC50 - Daphnia magna (Water flea) - > 479.7 mg/l - 48 h. and other aquatic Method: OECD Test Guideline 202 invertebrates Immobilization EC50 - Daphnia magna (Water flea) - 785 mg/l - 48 h Toxicity to algae Growth inhibition EC50 - Selenastrum capricornutum (green algae) - > 114.86 mg/l - 72 h. Method: OECD Test Guideline 201 Toxicity to bacteria Growth inhibition IC50 - other microorganisms - > 5,000 mg/l - 16 h.

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.

Hexane, 1,6-diisocyanato-, homopolymer cas#:(28182-81-2) [10-15%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

Butyl acetates cas#:(123-86-4) [5-10%]

Information on ecological effects

Toxicity: Toxicity to fish LC50 - Lepomis macrochirus (Bluegill) - 100 mg/l - 96 h. Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 72.8 - 205.0 mg/l - 24 h. and other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects. no data available

Benzene, 1-chloro-4-(trifluoromethyl)- cas#:(98-56-6) [25-35%] Information on ecological effects Toxicity: no data available Persistence and degradability: no data available Bioaccumulative potential: no data available Mobility in soil: no data available Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted Other adverse effects: no data available Acetone cas#:(67-64-1) [15-20%] Information on ecological effects Toxicity: no data available Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 13,500.00 mg/l - 48 h. other aquatic invertebrates Persistence and degradability: no data available Bioaccumulative potential: no data available Mobility in soil: no data available Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

# DISPOSAL CONSIDERATIONS

Propanoic acid, 3-ethoxy-, ethyl ester cas#:(763-69-9) [1-10%]

Waste treatment methods

13

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging: Dispose of as unused product.

Hexane, 1,6-diisocyanato-, homopolymer cas#:(28182-81-2) [10-15%]

Waste treatment methods

Product: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product.

Butyl acetates cas#:(123-86-4) [5-10%]

Waste treatment methods

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product.

Benzene, 1-chloro-4-(trifluoromethyl)- cas#:(98-56-6) [25-35%]

Waste treatment methods

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product.

Acetone cas#:(67-64-1) [15-20%]

Waste treatment methods

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product.

14	TRANSPORT INFORMATION
DOT	

UN Number:	UN 1263
UN Proper Shipping Name:	Paint
Transport Hazard Class(es)	
Class,	3
Label{s):	3
Packing Group:	II
Marine Pollutant:	Not regulated.
Special precautions for user:	
IMDG	
UN Number:	UN 1090
UN Proper Shipping Name:	
Transport Hazard Class(es)	
Class:	3
Label(s):	3
EmSNo.:	F-E, S-D
Packing Group:	II
Marine Pollutant:	Not regulated.

## **REGULATORY INFORMATION**

Component (CAS#) [%] - CODES

15

Propanoic acid, 3-ethoxy-, ethyl ester (763-69-9) [1-10%] TSCA

Hexane, 1,6-diisocyanato-, homopolymer (28182-81-2) [10-15%] TSCA

Butyl acetates (123-86-4) [5-10%] CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [25-35%] TSCA

RQ(5000LBS), Acetone (67-64-1) [15-20%] CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

#### **Regulatory CODE Descriptions**

\_\_\_\_\_

RQ = Reportable Quantity TSCA = Toxic Substances Control Act CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level HAP = Hazardous Air Pollutants NJHS = NJ Right-to-Know Hazardous Substances SARA313 = SARA 313 Title III Toxic Chemicals TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List) TXHWL = TX Hazardous Waste List

16 OTHER INFORMATION

## <u>Disclaimer</u>

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside of MC Crystal knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS MC Crystal AGREES OTHERWISE IN WRITING, MC Crystal MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. MC Crystal WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

## **End of Safety Data Sheet**

Revision Date: